

# Technical Information Sheet



## QuickSeam Batten Cover

Item Description	Item Number
6" (152.4 mm) x 100' (30.5 m)	W56RAC1616
9" (228.6 mm) x 100' (30.5 m)	W56RAC1619
12" (304.8 mm) x 50' (15.2 m)	W56RAC1624

### Description

QuickSeam Batten Cover is a semi-cured EPDM and QuickSeam Tape laminate designed to cover and seal batten strips and as specified by Elevate Specifications and Details.

### Method of Application

1. Use QuickPrime™ Plus and QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime the roofing components within the seaming area.
2. Center and apply the QuickSeam Batten Cover over the batten strip.
3. Refer to application instructions for specifics: [www.HolcimElevate.com](http://www.HolcimElevate.com)

### Storage

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

### Shelf Life

Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C). Shelf life will be shortened if exposed to elevated temperatures.

### Precautions

Refer to Safety Data Sheets (SDS) for additional safety information.

## Packaging

- 6" (152.4 mm) Roll - 2 rolls per carton – 36 cartons per pallet
- 9" (228.6 mm) Roll - 1 roll per carton – 36 cartons per pallet
- 12" (304.8 mm) Roll - 1 roll per carton – 36 cartons per pallet

## LEED® Information

Post-Consumer Recycled Content: 0%  
 Post Industrial Recycled Content: 0%  
 Manufacturing Location: Prescott, AR

NOTE: LEED® is a registered trademark of the U.S. Green Building Council



Typical Properties – QuickSeam Tape	
Properties	Value
Base	Rubber Polymers
Color	Black
Solvents	None
Solids	100%
Specific Gravity	98± 0.02 (H2O = 1)
Cured State	Cured
Thickness	0.035" (0.89 mm) ± 0.005" (0.127 mm)
Width	6.125" (155.6 mm) + 9.5 mm, - 0"

Typical Properties – EPDM Flashing	
Properties	Value
Base	EPDM
Color	Black
Solvents	None
Solids	100%
Cured State	Semi-Cured
Thickness	0.040" (1.016 mm) ± 0.017" – 0.007"
Width	6" (152.4 mm) + 0, - 0.125" (3.175 mm)

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.