

# Technical Information Sheet



## UltraPly™ TPO QuickSeam™ 9½" Flashing

Item Description	Item Number
White	W56TPO30T9
Gray	W56TPOG0T9
Tan	W56TPOT0T9

### Description

UltraPly TPO QuickSeam 9½" Flashing is an unsupported (non-reinforced) TPO membrane factory laminated to white seam tape. UltraPly TPO QuickSeam 9½" Flashing is used to flash gravel stops and other flashing applications as indicated in Elevate specifications and details.

### Method of Application

1. Use Elevate Single Ply QuickPrime™ Primer or Single Ply LVOC Primer applied with a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime membrane and metal mating surfaces to receive UltraPly QuickSeam 9½" Flashing.
2. Refer to current Elevate specifications for application instructions and details using Elevate UltraPly TPO QuickSeam 9½" Flashing: [www.HolcimElevate.com](http://www.HolcimElevate.com)

**NOTE:** UltraPly TPO QuickSeam products must be heat-formed to conform to seam step-offs, metal laps, angle changes, etc.

### Storage

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

### Shelf Life

Shelf life of 1.5 years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C). Shelf life will be shortened if exposed to elevated temperatures.

### Precautions

Refer to Safety Data Sheets (SDS) for additional safety information.

## LEED® Information

Post-Consumer Recycled Content: 0%  
 Post Industrial Recycled Content: 0%  
 Manufacturing Location: Michigan Center, MI  
**NOTE: LEED® is a registered trademark of the U.S. Green Building Council**



Typical Properties			
QuickSeam Tape		TPO Unsupported Flashing	
Properties	Value	Properties	Value
Base	Rubber Polymers	Base	TPO
Color	White	Color	White, Gray, Tan
Percent Solids	100%	Solvents	None
Specific Gravity	1.08 ± 0.03	Percent Solids	100%
Cured State	Cured	Specific Gravity	0.96 ± 0.02
Thickness	0.030" (0.76 mm) ± .005" (0.13 mm)	Thickness	0.030"(0.76 mm) ± 10%
Width	9¾" (248 mm) -0 /+ 1/16" (1.6 mm)	Width	9½" (241 mm) +0 / - 1/8" (3.18 mm)
Length	100' (30.5 m)	Length	100' (30.5 m)

Packaging	
Properties	Value
Roll	9.5" (235 mm) x 100' (30.48 m) roll
Carton	1 roll per carton
<b>NOTES:</b> QuickScrubber and/or QuickScrubber Plus Pads and Handles are included in each carton. Quantities vary depending on the QuickSeam product.	

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.