

Technical Information Sheet



UltraWhite Granules

Item Description	Item Number
Pail - UltraWhite Granules	W70RACGGNUW

Description

UltraWhite ceramic roofing granules are made available in 5-gallon plastic pails.

Method of Application

Elevate recommends that granules be applied to areas of asphalt “bleed-out” while the asphalt is still in a molten state. Areas of “bleed-out” at inside and outside corners require application of granules.

Precautions

Refer to Safety Data Sheets (SDS) for additional safety information.

LEED® Information

Post-Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Millen, GA

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Product Packaging	
Properties	Value
Pail	5 gal (18.9 L)
Pallet Size	48" x 39" (1.2 m x 1.0 m)
Pallet Weight	1,440 lb (653 kg)
Pails per Pallet	36
Pallets per Truckload	24

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.