

Technical Information Sheet



UNA-CLAD™ UC-14 Clip

Item Description	Item Number
Galvanized Steel	W6810C1417G
Stainless Steel	W6810C1417S

Description

UNA-CLAD UC-14 Clips are specially designed to be used in the attachment of the UNA-CLAD UC-14 Standing Seam Roof Panel. The design of the clip allows the upper tab to be mechanically integrated into the double lock seam.

Method of Application

1. Position the clips flush against the vertical seam.
2. Ensure clip is parallel with vertical seam.
3. Attach clips to roof deck using the appropriate fastener.
4. Position adjacent panel flush against installed clip.

NOTE: Install assembly according to Elevate Metal Design and Application Guides found on the Elevate website. Follow approved installation details.

Storage

Store in unopened original containers protected from the weather.

Packaging

250 clips per carton

Precautions

- Do not overdrive or underdrive fastener.
- Clips are designed to anchor UC-14 standing seam roof panels only.
- Cannot be used with fasteners larger than #12.
- Eye protection must be worn during the installation of fasteners.
- Clip allows for unlimited movement of the panel.

Stocking Location: Anoka, MN



Product Data	
Property	Value
Material	G-90 Galvanized or 304 2b Stainless Steel
Material Thickness	18 ga; 0.050" (1.27 mm)
Base	3.75" (95.25 mm) x 1.15" (29.21 mm)
Tab	3.50" (88.90 mm) x 1.875" (47.63 mm)
Hole Diameter	0.22" (5.59 mm)

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.