


Technical Information Sheet



PVC T-Joint Cover

Item Description	Item Number
White	W56PAW1005
Tan	W56PAT1005
Gray	W56PAG1005

Description

Elevate PVC T-Joint Covers are a flexible, non-reinforced, flashing membrane made with DuPont Elvaloy® KEE. They are designed to cover and seal T-joints formed at seam intersections and at angle changes 1:12 or greater for Elevate PVC and PVC KEE reinforced membranes.

Method of Application

1. Prepare T-joint area by removing all dirt and debris from membrane surface. Clean the surface area of the field sheet and the T-Joint Cover prior to installation of Elevate PVC T-Joint Covers.
2. Heat weld Elevate PVC T-Joint Covers in accordance with current Elevate PVC roofing specifications and details.

Storage

Store material in its original unopened packaging away from sources of physical damage or chemical contamination.

Precautions

- Refer to Safety Data Sheets (SDS) for additional safety information.
- Contact a Regional Technical Coordinator at 1-800-428-4511 for specific recommendations regarding chemical or waste product compatibility with Elevate PVC T-Joint Covers.

LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Hillside, NJ

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties		
Properties	ASTM Standard	Typical Performance
Membrane Thickness	D 751	0.055" (1.39 mm)
Tensile Strength	D 638	2,100 x 1,950 psi (14.48 x 13.44 MPa)
Elongation at Break	D 638	> 250%
Tearing Strength	D 1004	12 lbf (53.38 N)
Low Temperature Bend	D 2136	-40 °F (-40 °C)
Properties After Heat Aging (Retained Values) (176 ± 2 °F (116.80 ± 1 °C for 56 days ± 1 h)		
Tensile Strength	D 638	≥ 90% of original
Elongation at Break	D 638	≥ 90% of original

Product Data	
Material	DuPont Elvaloy KEE
Colors	White, Tan and Gray
Nominal Thickness	0.055" (1.39 mm)
Diameter	≥ 4.5" (114.3 mm)

Product Packaging	
Units per Carton	100
Weight per Carton	≤ 6 lb (2.7 kg)

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.